

Portable energy generator 22000W

¡NEW!

STXGGHG220L

SECURITY SYSTEM

High CO contamination alarm safety system or direct shutdown for low oil prevention.

PORTABILITY

A reinforced harness with high durability and stability, equipped with industrial-grade wheels to make transportation easier.



LARGER

FUEL TANK

Large capacity 40L fuel tank for higher performance

Easy to use panel with waterproof plug protectors



EASY ONE PULL START

High work efficiency.

COMMERCIAL GRADE ALTERNATOR

100% copper design.

LONG LIFESPAN

Durability of 600 hours.

FUEL EFFICIENCY

Low fuel consumption.

SPECIFICATIONS

Model No.	STXGGHG220L
Rated output power	17,500W
Maximum starting output wattage	22,000W
Engine type	Excitation motor
Engine displacement cc	999
Starting mode	Electric Start
ATS function	NO
CO alarm	NO
Noise (dB)	80
Electric start	INCLUDED
Wheels and handle	INCLUDED
Battery	INCLUDED
VFT	YES
Volume of oil	2 L
Fuel tank capacity	40 L
Net Weight (kgs):	213
Dimension (mm) (L x W x H):	1034x860x716
Container loading: 20'GP/ 40'HQ	32pcs / 66pcs
UPC code	810073477070

THE MEASURE OF A PRO™