

STANLEY®

GAS WATER HEATER 20LT/MIN CAPACITY

¡NEW!

STXGWHG20V

STANLEY



**STABLE COMBUSTION
CHAMBER SEALED**

**LOW WATER PRESSURE
START-UP**

SMART LED SCREEN

**Guarantees low
NOx emissions.
Less than 56 mg/kwh**



CONSTANT TEMPERATURE CONTROL

Combustion control system that detects water flow and sends signals to the ignition sensor and gas valve, allowing a continuous supply of water at constant temperature.

OXYGEN-FREE COPPER HEAT EXCHANGER

The advanced heat exchanger provides efficient and fast heating, meets ERP 'A' energy class and ensures a long service life and a more hygienic environment.

ALUMINUM GAS DISTRIBUTOR AND COPPER NOZZLES

Special individual gas distribution tubes manufactured in lightweight aluminum and copper injectors that mix enough gas and air to achieve low NOx emissions.

SPECIFICATIONS

Model No.	STXGWHG20V
Voltage	220V~
Frequency	60Hz
Rated thermal power	40,000W
Heating element material	Stainless Steel
Material of the lining tank	Oxygen free copper heat exchanger
Outer Cover Material	Steel plate with coating
IP Rating	IPX2
Efficiency	≥ 84%
Consumption	NG-4 m3/h
Ignition mode	Pulse ignition
Capacity	20 L
Temperature control range	Digital
Exhaust type	Forced
Net Weight	20 kg
Product Dimensions	570x395x185 mm
Packaging Dimensions	695x465x255 mm
UPC Code	810073477582

THE MEASURE OF A PRO™